SAFETY MANUAL		
Document Number:	L030601	
Revision:	1	
Date of Origin:	Jan 1,2024	
Manual:	SM-AAC	
Page:	1 of 9	

SAFETY DATA SHEET

1.0 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Purple Lubricant - Fragrance

Manufacturer: Metlab Corporation
Address: 4011 Hyde Park Blvd
City, State, Zip Niagara Falls NY 14305

Phone Number: 800-828-6866 Emergency Phone: 888-255-3924

Hazardous Spill Response:

2.0 HAZARD IDENTIFICATION

GHS Classification: Hazardous

Flammable Liquid Category 2 – H226 Acute Toxicity Category 3 – H332 Aspiration Toxicity Category 3 – H305

IDLH (Immediate Danger to Life and Health): None

Physical Hazards: Not Classified

Health Hazards:

Specific Target Organ Toxicity - Lungs: Single Exposure Category 3

Label Elements:



Flammable



Acute Toxicity



Aspiration Hazard

Signal Word: Danger Hazard Statement(s):

H226: Flammable Liquid and Vapour

H305: May be harmful if swallowed and enters airways

H332: Harmful if inhailed

P210: Keep away from heat, sparks, open flames, hot surfaces. - No smoking

P233: Keep container tightly closed

P240: Ground/bond container and receiving equipment

P241: Use explosion-proof electrical, ventilating, lighting equipment

P242: Use only non-sparking tools

P243: Take precautionary measures against static discharge

P261: Avoid breathing mist, vapors, spray

P271: Use only outdoors or in a well-ventilated area

P280: Wear protective gloves, protective clothing, eye protection, face protection

	SAFETY MANUAL	
	Document Number:	L030601
	Revision:	1
	Date of Origin:	Jan 1,2024
SAFETY DATA SHEET	Manual:	SM-AAC
SAFETY DATA SHEET	Page:	2 of 9

Precautionary Response:

P301+P310; IF SWALLOWED: immediately call a POISON CENTER or doctor/physician

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P331 - If swallowed, do NOT induce vomiting

P370+P378: In case of fire: Use carbon dioxide (CO2), powder, alcohol-resistant foam for extinction

P403+P233: Store in a well-ventilated place. Keep container tightly closed

P403+P235: Store in a well-ventilated place. Keep cool

P501: Dispose of contents/container to comply with local, state and federal regulations

3.0 Composition & Hazardous Ingredients

The terms "hazardous" and "hazardous materials" as used within this SDS (EU - MSD) should be interpreted as defined by, and accordance with, the OSHA Hazard Communication Standard (29 CFR 1910:1200) and the EU Occupational Exposure Limits (OEL) REGULATION (EC) No 1272/2008 including cited Appendices, Lists, References, etc., all of which are hereby incorporated by reference and stated below as appropriate.

OECD SIDS documents published by UNEP Chemicals in response to its mandate to facilitate the access to information needed for health and environmental risk assessment of chemicals. The documents contain the information gathered and an Initial Assessment performed under the framework of the OECD HPV Chemicals Programme.

Substance	CAS Number	EC Number	Percent by Weight
Ethanol	64-17-5	200-578-6	30.0% - 69.0%
Proprietary Non-Haz Ingredients	N/A	N/A	25.0% - 68.0%
Proprietary Non-Haz Fragrance	N/A	N/A	0.0% - 1.0%
Proprietary Non-Hazardous Dye	N/A	N/A	0.0% - 1.0%

Hazardous Mixtures: None

(See Section 8.0 for Occupational Exposure Limits)

4.0 FIRST AID MEASURES

First-aid measures general: Check the vital functions. Unconscious: maintain adequate airway and

respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition:

doctor/hospital.

First-aid measures after inhalation: If inhaled, remove to fresh air and keep at rest in a position comfortable for

breathing. Obtain medical attention if breathing difficulty persists.

First-aid measures after skin contact: Rinse immediately with plenty of water. Gently wash with plenty of soap and

water. Obtain medical attention if irritation persists.

First-aid measures after eye contact: Immediately rinse with water for a prolonged period while holding the eyelids

wide open. Seek medical attention if material is embedded in eye. If eye

irritation persists: Get medical advice and attention.

First-aid measures after ingestion: If swallowed, do not induce vomiting: seek medical advice immediately and

show this container or label.

Symptoms/injuries: Repeated or prolonged inhalation may damage lungs.

	SAFETY MANUAL	
	Document Number:	L030601
	Revision:	1
	Date of Origin:	Jan 1,2024
SAFETY DATA SHEET	Manual:	SM-AAC
	Page:	3 of 9

Symptoms/injuries after inhalation: May cause irritation to the respiratory tract, sneezing, coughing, burning

sensation of throat with constricting sensation of the larynx and difficulty in

breathing. Dizziness. Headache. Narcosis.

Symptoms/injuries after skin contact: Dry Skin. Redness and cracking of the skin.

Symptoms/injuries after eye contact: Redness, pain.

Symptoms/injuries after ingestion: Ingestion of large amounts may produce gastrointestinal disturbances

including irritation, nausea, and diarrhea.

Chronic symptoms: Respiratory difficulties and lung damage.

5.0 FIRE-FIGHTING MEASURES

Fire Hazard: Flammable

Extinguishing Media: Use BC type fire extinguisher, or Carbon Dioxide in a large area.

Special Firefighting Procedures: Typical for gasoline or other flammable fuels.

Unusual Fire and Explosion Hazards: Gas and vaporare explosive with air within explosion limits.

Reactivity: Upon combustion, CO and CO2 are formed.

Protective Equipment for Firefighting: S

Protection During Firefighting:

Due a set i su a ser Management Fina

Self-Contained Breathing Apparatus and clothing for chemical fires.

Use normal individual fire protective equipment.

Precautionary Measures Fire: Exposure to fire / heat: keep upwind. Exposure to fire / heat: consider

evacuation. Exposure to fire / heat: seal off low-lying areas. Exposure to fire /

heat: have residence shelter in place.

6.0 ACCIDENTAL RELEASE MEASURES

Personal Precautions / Protective Equipment:

Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Do not breathe vapor, gas, fume or spray. Ventilate area or wear SCBA.

Environmental Precautions: Prevent further leakage or spillage and comply with local, state and federal regulations. **Methods / Materials for Containment & Clean-up:**

Mark the danger area. Stop engines and no smoking. No naked flames or sparks. Spark- and explosion proof appliances and lighting equipment. Wash contaminated clothes.

Large Spills: Dike the spilled area. Absorb with vermiculite, dry sand or earth and place into containers. Flush area with water and dispose accordingly. Section 13 of this SDS.

Small Spills: Absorb with vermiculite, dry sand or earth and place into containers. Flush area with water and dispose accordingly.

7.0 HANDLING & STORAGE

Precautions for Safe Handling:

Wear suitable protective clothing and eye/face protection. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Keep container tightly closed. Avoid breathing spray or mist.

Conditions for Safe Storage:

Store in original tightly closed container. Keep away from food, drink and animal feeding stuffs. Use care in handling / storage. Take precautions against electrostatic charges. Keep away from open flames / heat. Keep away from ignition sources / sparks. Avoid prolonged and repeated contact with skin. Keep container tightly closed. Measure the concentration in the air regularly. Work under local exhaust / ventilation. Store in accordance with local / regional / national / international regulation. SUITABLE CONTAINER: stainless steel, carbon steel, polyethylene, polypropylene.

	SAFETY MANUAL	
	Document Number:	L030601
	Revision:	1
	Date of Origin:	Jan 1,2024
SAFETY DATA SHEET	Manual:	SM-AAC
	Page:	4 of 9

8.0 Exposure Controls & Personal Protection

Control Parameters

Ethanol - 64-17-5

ACGIH TWA (mg/m³) 1000 mg/m³

ACGIH STEL 1000 mg/m³ ACGIH TLV 1000 mg/m³

NIOSH REL (TWA) (mg/m³) 1000 ppm OSHA PEL (TWA) (mg/m³) 1900 ppm

(Air Contaminates)

IDLH (mg/m³) Not Available

OECD SIDS UNEP TLV Not Available BAuATRGS 900 Not Available

TLV: Threshold Limit Value of a chemical substance is a level to which it is believed a worker can be exposed day after day for a working lifetime without adverse health effects.

TWA: (Time Weighted Average - TLV-TWA): average exposure on the basis of a 8h/day, 40h/week work schedule **STEL**: (Short Term Exposure Level) is an employee's 15-minute time weighted average exposure at any time during a work day and cannot be repeated more than 4 times in a day.

Personal Protective Equipment: Wear chemical resistant clothing, chemical goggles and chemical resistant gloves while handling under normal conditions.











Respiratory Protection: In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment. Use an appropriate NIOSH approved respirator if airborne fume concentrations exceed the appropriate PEL or TLV. Wear air supplied respiratory protection if exposure concentrations are unknown. All requirements set forth in 29CFR1910.134 must be met.

Protective Gloves: Butyl Rubber and Nitrile gloves are recommended. Be cautious as the liquid may penetrate the glove. Frequent change is advisable.

Ventilation: Use local exhaust ventilation which is adequate to limit personal exposure to airborne fumes to levels which do not exceed the appropriate PEL or TLV. If such equipment is not available, use respiratory protection as specified above.

Eye protection: Chemical / splash goggles are recommended. Eye wash station must be present.

Other Equipment: None

	SAFETY MANUAL	
	Document Number:	L030601
	Revision:	1
	Date of Origin:	Jan 1,2024
SAFETY DATA SHEET	Manual:	SM-AAC
	Page:	5 of 9

9.0 Physical and Chemical Properties

Appearance and Odor: Liquid, Fragrance + Alcohol

Color: Purple Physical State: Liquid

pH: Not Available
Viscosity: Not Available
Specific Gravity: Not Available
Vapor Density: Not Available
Vapor Pressure: Not Available
Melting Point: Not Applicable

Boiling Point: 185 F

Flash Point: 68 F Closed Cup
Freezing Point: Not Available
Percent Volatility: Not Available
Evaporation Rate (baC=1) Not Available

Solubility in Water: Completely Soluable

Solubility in Oil: Not Soluable Solubility in Solvents: Not Available

10.0 STABILITY AND REACTIVITY

Reactivity: Hazardous reaction will not occur under normal conditions.

Stability: This composition is stable under normal conditions.

Incompatibility (materials to avoid): Strong Oxidizers, Peroxides, Ammonia, Alkali Metals

Hazardous Decomposition Products: Carbon and Nitrogen Oxides.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Strong oxidizing agents. Heat, flames and sparks. Avoid temperatures exceeding the flash point

11.0 TOXICOLOGICAL INFORMATION

Ethanol – 64-17-5

Acute Toxicity - Oral - LD50 - 7060 mg/kg (Rat)

Acute Toxicity – Dermal - LD50 – No Data

Acute Toxicity – Inhalation - LD50 – 20,000 mg/kg (10H) (Rat)

Acute Toxicity: Toxic if inhaled

Skin Corrosion / Irritant: Irritating to skin.

Serious Eye Damage / Irritant: Eye Irritant

Respiratory / Skin Sensitisation: Not Classified

Germ Cell Mutagenicity: Not Classified

Carcinogenicity: Not Classified

	SAFETY MANUAL	
	Document Number:	L030601
	Revision:	1
	Date of Origin:	Jan 1,2024
CAPETY DATA CHEET	Manual:	SM-AAC
SAFETY DATA SHEET	Page:	6 of 9

Reproductive Toxicity: Humand, Female, Oral – Neonatal Measures or Effects.

Target Organ Toxicity (Single Exposure): May cause respiratory / skin irritation.

Target Organ Toxicity (Repeated Exposure): May adversly affect the liver and kidney based on animal testing.

Aspiration Hazard: Toxic if inhaled

Teratogenicity: Avoid contact during pregnancy or while nursing.

12.0 ECOLOGICAL INFORMATION

Ethanol – 64-17-5

Aquatic:

Fish – LC50 – No Data Available Fish – EC50 – No Data Available

Threshold Limit Algea - No Data Available

Ecotoxicity:No information available

Persistence and Degradability: No information available

Bioaccumulative Potential: No information available

Mobility in Soil: No information available

Other Adverse Effects: Environmental hazards cannot be excluded by inappropriate handling or disposal.

13.0 DISPOSAL CONSIDERATION

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle by distillation. Do not landfill. Incinerate under surveillance with energy recovery. Do not discharge into drains or the environment. Use appropriate containment to avoid environmental contamination.

Dispose in a safe manner in accordance with local, state and federal regulations.

14.0 Transport Information

Packing Group:

IMO Classification:

US DOT Classification: 3 – Flammable and Combustable

Proper Shipping Name: Flammable Liquids, N.O.S (Ethanol Mixture)

UN Number: UN1993

Label: 3 – Flammable Liquids

Reportable Quantity: Not Reportable

Hazard Class:

3.2 - Flammable Liquid

IMO PSN Code: GPL

	SAFETY MANUAL	
	Document Number:	L030601
	Revision:	1
	Date of Origin:	Jan 1,2024
SAFETY DATA SHEET	Manual:	SM-AAC
	Page:	7 of 9

IMO Proper Shipping Name: Flammable Liquids, N.O.S (Ethanol Mixture)

IMO Regulation Page Number:N/AIMO UN Number:1993IMO UN Class:3.2

IATA Classification: 3 – Flammable Liquids

IATA PSN Code: N/A

IATA Proper Shipping Name: Flammable Liquids, N.O.S (Ethanol Mixture)

IATA UN ID Number: 1993
IATA UN Class: 3

IATA Label: Flammable Liquids, N.O.S (Ethanol Mixture)

DOT Passenger Aircraft Limitations: 5 L
DOT Cargo Aircraft Limitations: 60 L

DOT Special Provisions (49 CFR 172.102): None

15.0 REGULATORY INFORMATION

U.S. Federal Regulations:

Comprehensice Environmental Response Compensation and Liability Act of 1980 (CERCLA):

No reportable quantity for this product.

Toxic Substance Control Act (TSCA):

All of the components of this material are listed on the TSCA Chemical Subtances Inventory.

Clean Water Act (CWA):

Listed under sections of the Clean Water Act. CWA Section 1321. Contact your local / state authorities to determine if substances are regulated under their jurisdiction.

Clean Air Act (CAA):

Listed under various sections of the Clean Air Act. Contact your local / state authorities to determine if substances are regulated under their jurisdiction.

Superfund Amendments and Reauthorization Act (SARA) Title III Information:

This product contains chemicals subject to annual release reporting requirements Under SARA Title III, Section 313 (40 CFR 372). Fire Hazard.

EUROPEAN / INTERNATIONAL REGULATIONS:

Control of Substances Hazardous to Health (COSHH):

Component(s) are listed under various sections of the COSHH regulation. Contact your local authorities to determine if substances are regulated under their jurisdiction.

Scottish Environmental Protection Agency (SEPA):

Component(s) are listed under various sections of SEPA. Contact your local authorities to determine if substances are regulated under their jurisdiction.

Canada:

Components are listed on the Canadian DSL (Domestic Sustances List) inventory.

WHMIS Classification:

Class B Division 3 – Combustible Liquid

Class D Division 2 Subdivision B – Toxic material causing other toxic effects.

Hazard Classification

European Union Directives 67/548/EEC and 1999/45/EC

	SAFETY MANUAL	
	Document Number:	L030601
	Revision:	1
	Date of Origin:	Jan 1,2024
SAFETY DATA SHEET	Manual:	SM-AAC
	Page:	8 of 9

Safety Phrases: S 23 Do not breathe fumes

S 24/25 Avoid contact with skin and eyes.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S 22 D

S 26 In

S 38 In

S 36 W

S 38 In case of insufficient ventilation wear suitable respiratory equipment.

S 36 Wear suitable protective clothing.

R10, Xnl R65m R66, R67

U.S. STATE REGULATORY INFORMATION: The components of these products are covered under specific State regulations, as denoted below:

New Jersey Right to Know Components: Ethanol 64-17-5

CALIFORNIA PROPOSITION 65: This product does not contain chemicals regulated under California Proposition 65.

International Air Transport Authority (IATA): Hazardous air transport. See Section 14

16.0 OTHER INFORMATION

NFPA health hazard

2 - Can cause temporary incapacitation or residual injury.

NFPA fire hazard NFPA reactivity

3 – Can be ignited under almost all ambient temperature conditions.

 $\ensuremath{\text{0}}$ - Normally stable, even under fire exposure conditions, and are not reactive with

water.



HMIS III Rating

 $\begin{array}{lll} \mbox{Health} & 2 - \mbox{Moderate Hazard} \\ \mbox{Flammability} & 3 - \mbox{High Hazard} \\ \mbox{Physical} & 0 - \mbox{Minimal Hazard} \\ \end{array}$

Personal Protection H

Reference:

UNEP Publications, OECD SIDS, Chemical Abstract Search (CAS) Database, European Chemicals Agency (ECHA), Workplace Hazard Material Information System (WHMIS)

Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; ADR/RID = European Agreement of Dangerous Goods by Road/Rail; DFG = Deutsche Forschungsgemeinschaft; DOT = Department of Transportation; DSL = Domestic Substances List; EEC = European Economic Community; EINECS = European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EU = European Union; WHMIS=Workplace Hazard Material Information System; HMIS = Hazardous Materials Identification System; IARC = International Agency for Research on Cancer; IMO = International Maritime Organization; IATA = International Air Transport Association; MAK = Maximum Concentration Value in the Workplace; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Association; NTP = National Toxicology Program; STEL = Short-term Exposure Limit; TDG = Transportation of Dangerous Goods; TSCA = Toxic Substances Control Act; TWA = Time Weighted Average

	SAFETY MANUAL	
	Document Number:	L030601
	Revision:	1
	Date of Origin:	Jan 1,2024
SAFETY DATA SHEET	Manual:	SM-AAC
SAFETY DATA SHEET	Page:	9 of 9

DISCLAIMER

The statements, information, and data provided in this Safety Data Sheet are believed reliable and accurate by Metlab Corporation and its responsible personnel. However, no other guarantee, representation, warranty or responsibility is expressed or implied to any user, regardless of reliance on all or any part thereof. This includes warranties or merchantability or of fitness for a particular purpose, and Metlab Corporation assumes no responsibility whatsoever for advice or recommendations made herein. Nothing contained herein should be interpreted as permission, inducement, or condonement to violate any law pursuant to this product's use, conveyance or disposal.