JAN 2024

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
 - Trade name: Technovit 4006 liquid
 - · Relevant identified uses of the substance or mixture and uses advised against
 - · Application of the substance / the preparation Resin for metallographic testing
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

Heraeus Kulzer GmbH

Grüner Weg 11, D-63450 Hanau Tel.: 06081 959-365 (Wehrheim)

· Informing department:

Stefan Schreier

Tel.: +49 6081 959-367 Fax: +49 6081 959-398

email: stefan.schreier@heraeus.com

Emergency telephone number:

Call "Poisining Emergency Center Berlin": +49 30 30686 790 (24 hours, support in english and german language)

2 Hazards identification

- · Classification of the substance or mixture
 - · Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.



Xi: Sensitising

R43: May cause sensitisation by skin contact.



F; Highly flammable

R11: Highly flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification"

guideline for preparations of the EU" in the latest valid version. Classification system:

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

- · Label elements
 - Labelling according to EU guidelines:

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)

· Code letter and hazard designation of product:

Xi Irritant

F Highly flammable

· Hazard-determining components of labelling: methyl methacrylate

· Risk phrases:

11 Highly flammable.

36/37/38 Irritating to eyes, respiratory system and skin.

43 May cause sensitisation by skin contact.

Safety phrases:

9 Keep container in a well-ventilated place.

(Contd. on page 2)

JAN 2024

Trade name: Technovit 4006 liquid

(Contd. of page 1)

- 1■Keep away from sources of ignition No smoking.
- 23 Do not breathe fumes.
- 24 Avoid contact with skin.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 37 Wear suitable gloves.
- · Other hazards
 - · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
 - · Description: Product based on methacrylates

· Dangerous components:			
CAS: 80-62-6 EINECS: 201-297-1		Xi R37/38; Xi R43; F R11	> 90%
CAS: 79-41-4 EINECS: 201-204-4		C R35; Xn R21/22	0-5%

· Additional information For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
 - · After inhalation Supply fresh air; consult doctor in case of symptoms.
 - · After skin contact instantly wash with water and soap and rinse thoroughly.
 - After eye contact
 - Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
 - After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

Product based on methacrylates

5 Firefighting measures

- Extinguishing media
 - · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
 - For safety reasons unsuitable extinguishing agents Water.
- · Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
 - · Protective equipment: No special measures required.
- · Additional information -

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 - Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Do not flush with water or aqueous cleansing agents

(Contd. on page 3)

JAN 2024

Trade name: Technovit 4006 liquid

(Contd. of page 2)

Send for recovery or disposal in suitable containers.

Reference to other sections

See Section 13 for information on disposal.

See Section 8 for information on personal protection equipment.

7 Handling and storage

·Handling

Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

- Storage
 - · Requirements to be met by storerooms and containers: Store in cool location.
 - Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions:

Store cool (not above 25 °C).

Store in cool, dry conditions in well sealed containers.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with critical values that require monitoring at the workplace:

80-62-6 methyl methacrylate

OES Short-term value: 416 mg/m³, 100 ppm

Long-term value: 208 mg/m³, 50 ppm

79-41-4 methacrylic acid

OES Short-term value: 143 mg/m³, 40 ppm

Long-term value: 72 mg/m³, 20 ppm

· Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

Personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

Protection of hands:

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

(Contd. on page 4)

JAN 2024

Trade name: Technovit 4006 liquid

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

 PVA gloves
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton) Chloroprene rubber, CR Butyl rubber, BR Nitrile rubber, NBR

- · Eye protection: Protective goggles are recommended.
- · Body protection: Light weight protective clothing

9 Physical and chemical pr	operties	
Information on basic physical General Information Appearance: Form: Colour: Smell:	and chemical properties Fluid Colourless Characteristic	
Change in condition Melting point/Melting ran Boiling point/Boiling ran	nge: Not determined ge: 100°C	
· Flash point:	10°C	
· Ignition temperature:	430°C	
· Self-inflammability:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air, vapour mixtures is possible.	
Critical values for explosion Lower: Upper:	n: 2.N Vol % 1∎ Vol %	
· Steam pressure at 20°C:	47 hPa	
· Density at 20°C	0.95 g/cm³	
· Solubility in / Miscibility wit · Water:	h Not miscible or difficult to mix	
· Viscosity: · dynamic at 20°C:	1 mPas	

(Contd. on page 5)

JAN 2024

Trade name: Technovit 4006 liquid

(Contd. of page 4)

· Solvent content:

Water: 0.2 %

10 Stability and reactivity

- · Reactivity
 - · Chemical stability
 - · Conditions to be avoided: No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known
- · Hazardous decomposition products: None
- · Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:
 - Primary irritant effect:
 - on the skin: Irritant for skin and mucous membranes.
 - · on the eye: Irritant effect.
 - · Sensitization: Sensitization possible by skin contact.
 - · Additional toxicological information:

Irritant

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

· Sensitisation May cause sensitisation by skin contact.

12 Ecological information

- · Toxicity
 - · Acquatic toxicity: No further relevant information available.
- · Additional ecological information:
 - · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

- · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Śmall quantities can be polymerized with the matching system component(s) and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities.

· European waste catalogue

1∎01 06 chemicals consisting of or containing dangerous substances

(Contd. on page 6)

JAN 2024

Trade name: Technovit 4006 liquid

(Contd. of page 5)

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)



· ADR/RID-GGVS/E Class: 3 (F1) Flammable liquids.

· Kemler Number: 339 · UN-Number: 1247 · Packaging group: || · Label 3

· UN proper shipping name: 1247 METHYL METHACRYLATE MONOMER, STABILIZED,

solution

· Maritime transport IMDG/GGVSea:



· IMDG/GGVSea Class: 3
· UN Number: 1247
· Label 3
· Packaging group: ||
· EMS Number: F-E,S-D

· Marine pollutant: No

· Correct technical name: METHYL METHACRYLATE MONOMER, STABILIZED, solution

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3
· UN/ID Number: 1247
· Label 3
· Packaging group: ||

· Correct technical name: METHYL METHACRYLATE MONOMER, STABILIZED, solution

- · Special precautions for user Warning: Flammable liquids.
- · Transport/Additional information: -

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

None of the ingredients is listed.

(Contd. on page 7)

JAN 2024

Trade name: Technovit 4006 liquid

(Contd. of page 6)

· Standard for the Uniform Scheduling of Drugs and Poisons

None of the ingredients is listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases R11 Highly flammable.

R21/22 Harmful in contact with skin and if swallowed.

R35 Causes severe burns.

R37/38 Irritating to respiratory system and skin.

May cause sensitisation by skin contact.

· Contact:

Dr. Thiele Tel.: (+49) 6181 35-3012 email: ruediger.thiele@heraeus.com

* Data compared to the previous version altered.