JAN 2024

#### 1 Identification of substance

- · Product details
  - Trade name: Technovit 5000 powder
    - · Application of the substance / the preparation Resin for metallographic testing
  - Manufacturer/Supplier:

Heraeus Kulzer GmbH

Grüner Weg 11, D-63450 Hanau Tel.: 06081 959-365 (Wehrheim)

Informing department:

Stefan Schreier

Tel.: +49 6081 959-367 Fax: +49 6081 959-398

email: stefan.schreier@heraeus.com

Emergency information: Call "Poisining Emergency Center Berlin": +49 30 30686 790 (24 hours, support in english and german language)

#### 2 Hazards identification

- · Hazard designation: void
- Information pertaining to particular dangers for man and environment

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

#### 3 Composition/information on ingredients

- · Chemical characterization
  - Description: -
  - · Dangerous components: Void
  - · Additional information For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

- · General information No special measures required.
- · After skin contact The product is not skin irritating.
- After eye contact Rinse opened eye for several minutes under running water.
- After swallowing Initiate vomiting and consult a doctor.

### 5 Fire fighting measures

- · Suitable extinguishing agents
- CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- · Protective equipment: No special measures required.
- Additional information -

#### 6 Accidental release measures

- · Person-related safety precautions: Not required.
- · Measures for environmental protection: No special measures required.
- · Measures for cleaning/collecting: Collect mechanically.

(Contd. on page 2)

JAN 2024

## Trade name: Technovit 5000 powder

· Additional information:

(Contd. of page 1)

No dangerous materials are released.

See Section 8 for information on personal protection equipment.

## 7 Handling and storage

- · Handling
  - · Information for safe handling: No special measures required.
  - Information about protection against explosions and fires: No special measures required.
- · Storage
  - · Requirements to be met by storerooms and containers: No special requirements.
  - Information about storage in one common storage facility: Not required.
  - Further information about storage conditions: Store cool (not above 25 °C).

#### 8 Exposure controls and personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Components with critical values that require monitoring at the workplace:

#### 7440-50-8 copper

OES () Short-term value: 2\*\* mg/m³ Long-term value: 0.2\* 1\*\* mg/m³

\*fume \*\*dusts and mists

- Additional information: The lists that were valid during the compilation were used as basis.
- · Personal protective equipment
  - General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

- · Breathing equipment: Not required.
- · Protection of hands: Not required.
  - · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: not absolutely neccessary
- · Body protection: Light weight protective clothing

#### 9 Physical and chemical properties:

#### · General Information

· Form: Powder

· Colour: Copper coloured · Smell: Copper soloured

Change in condition

· Melting point/Melting range: 1083°C

· Boiling point/Boiling range: Not determined

· Flash point: Not applicable

· Self-inflammability: Product is not selfigniting.

(Contd. on page 3)

JAN 2024

## Trade name: Technovit 5000 powder

|  |                           | (Contd. of page 2) |
|--|---------------------------|--------------------|
| Danger of explosion:                         | Product is not explosive. |                    |
| · Steam pressure at 20°C:                    | 0 mbar                    |                    |
| · Density at 20°C                            | 8.960 g/cm³               |                    |
| · Solubility in / Miscibility wi<br>· Water: | th<br>Unsoluble           |                    |
| · Solvent content:                           |                           |                    |
| · Solids content:                            | 1■ %                      |                    |

#### 10 Stability and reactivity

- · Conditions to be avoided: No decomposition if used and stored according to specifications.
- Dangerous reactions No dangerous reactions known
- · Dangerous products of composition: None

#### 11 Toxicological information

- · Acute toxicity:
  - Primary irritant effect:
    - on the skin: No irritant effect.
      on the eye: No irritant effect.
  - · Sensitization: No sensitizing effect known.
- Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

#### 12 Ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

#### 13 Disposal considerations

- · Product:
  - · Recommendation

Small quantities can be polymerized with the matching system component(s) and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities.

- · European waste catalogue
- 11 01 98 other wastes containing dangerous substances
- · Uncleaned packagings:
  - · Recommendation: Packaging can be reused or recycled after cleaning.

GB

JAN 2024

Trade name: Technovit 5000 powder

(Contd. of page 3)

## 14 Transport information

· Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)



· ADR/RID-GGVS/E Class: 9 (M7) Miscellaneous dangerous substances and articles.

Kemler Number: 90 3077 · UN-Number: · Packaging group: III· Label

Designation of goods: 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (copper)

· Maritime transport IMDG/GGVSea:



· IMDG/GGVSea Class: 3077 · UN Number: · Packaging group: Ш Marine pollutant: Yes

· Correct technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(copper)

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3077 · UN/ID Number: · Packaging group: Ш

· Correct technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(copper)

· Transport/Additional information: -

#### 15 Regulatory information

· Designation according to EC guidelines:

Observe the normal safety regulations when handling chemicals The product is not subject to classification according to the calculation methods of the "General Classification Guideline for Preparations of the EC" as issued in the last version. The product is not subject to identification regulations under EC Directives and the Ordinance on Hazardous Materials (GefStoffV).

#### 16 Other information:

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 5)

JAN 2024

## Trade name: Technovit 5000 powder

(Contd. of page 4)

Contact:
Dr. Thiele Tel.: (+49) 6181 35-3012
email: ruediger.thiele@heraeus.com

\* Data compared to the previous version altered.

JAN 2024

#### 1 Identification of substance

- · Product details
  - Trade name: Technovit 5000 liquid
    - · Application of the substance / the preparation Resin for metallographic testing
  - Manufacturer/Supplier:

Heraeus Kulzer GmbH

Grüner Weg 11, D-63450 Hanau Tel.: 06081 959-365 (Wehrheim)

Informing department:

Stefan Schreier

Tel.: +49 6081 959-367 Fax: +49 6081 959-398

email: stefan.schreier@heraeus.com

Emergency information: Call "Poisining Emergency Center Berlin": +49 30 30686 790 (24 hours, support in english and german language)

#### 2 Hazards identification

· Hazard designation:





Xi Irritant F Highly flammable

Information pertaining to particular dangers for man and environment

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Highly flammable.

R 37/38 Irritating to respiratory system and skin.

May cause sensitisation by skin contact. R 43

Classification system

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

#### 3 Composition/information on ingredients

- · Chemical characterization
  - **Description:** Product based on methacrylates

| · Dangerous com                      | ponents:  |        |
|--------------------------------------|---|--------|
|                                      | methyl methacrylate<br>Xi, F; R 11-37/38-43   | 50-75% |
|                                      | Epoxyacrylat<br>Xi; R 36  | 10-25% |
| CAS: 42978-66-5<br>EINECS: 256-032-2 | (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate<br>Xi, N; R 36/37/38-43-51/53 | 0-5%   |

<sup>·</sup> Additional information For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

(Contd. on page 2)

JAN 2024

## Trade name: Technovit 5000 liquid

· After swallowing Product based on methacrylates

(Contd. of page 1)

#### 5 Fire fighting measures

- · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents Water.
- Special hazards caused by the material, its products of combustion or flue gases:

Can form explosive gas-air mixtures.

- Formation of toxic gases is possible during heating or in case of fire.
- Protective equipment: No special measures required.
- · Additional information -

#### 6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection:

Prevent material from reaching sewage system, holes and cellars.

Measures for cleaning/collecting:
Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Do not flush with water or aqueous cleansing agents

Additional information:

No dangerous materials are released.

See Section 8 for information on personal protection equipment.

## 7 Handling and storage

- · Handling
  - Information for safe handling:

Wear protective equipment. Keep unprotected persons away.

Keep containers tightly sealed.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- - Requirements to be met by storerooms and containers: Store in cool location.
  - · Information about storage in one common storage facility: Not required.
  - · Further information about storage conditions:

Store cool (not above 25 °C).

Store in cool, dry conditions in well sealed containers.

## 8 Exposure controls and personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Components with critical values that require monitoring at the workplace:

#### 80-62-6 methyl methacrylate

OES () Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

- · Additional information: The lists that were valid during the compilation were used as basis.
- · Personal protective equipment
  - General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

(Contd. on page 3)

JAN 2024

## Trade name: Technovit 5000 liquid

(Contd. of page 2)

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

Protection of hands:

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

PVA gioves

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Chloroprene rubber, CR

- Eye protection: Protective goggles are recommended.
- · Body protection: Light weight protective clothing

| · General Information   |  |
|---|--|
| · Form:<br>· Colour:<br>· Smell:  | Fluid<br>Colourless<br>Characteristic  |
| · Change in condition<br>· Melting point/Melting i<br>· Boiling point/Boiling r |  |
| · Flash point:  | 10°C   |
| · Ignition temperature:   | 430.0°C  |
| · Self-inflammability:  | Product is not selfigniting.   |
| · Danger of explosion:  | Product is not explosive. However, formation of explosive air/vapour mixtures is possible. |
| · Critical values for explos  | ion:   |
| Lower:<br>Upper:  | 2.N Vol %<br>1■5 Vol %   |

(Contd. on page 4)

JAN 2024

## Trade name: Technovit 5000 liquid

|  |                                      | (Contd. of page 3) |
|--|--------------------------------------|--------------------|
| · Steam pressure at 20°C:                      | 47.0 hPa                             |                    |
| · Density at 20°C                              | 1 <b>■</b> g/cm³                     |                    |
| · Solubility in / Miscibility with<br>· Water: | th  Not miscible or difficult to mix |                    |
| · Viscosity:<br>· dynamic at 20°C:             | 50 mPas                              |                    |

### 10 Stability and reactivity

- · Conditions to be avoided: No decomposition if used and stored according to specifications.
- · Dangerous reactions No dangerous reactions known
- · Dangerous products of composition: None
- · Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

#### 11 Toxicological information

- · Acute toxicity:
  - Primary irritant effect:
    - · on the skin: Irritant for skin and mucous membranes.
    - · on the eye: Irritant effect.
    - Sensitization:

Sensitizing effect by skin contact is possible by prolonged exposure.

Sensitization possible by skin contact.

· Additional toxicological information:

Irritant

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

· Sensitisation May cause sensitisation by skin contact.

## 12 Ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

#### 13 Disposal considerations

- · Product:
  - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Śmall quantities can be polymerized with the matching system component(s) and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities.

· Waste disposal key number: 55370

· European waste catalogue

11 01 98 other wastes containing dangerous substances

(Contd. on page 5)

JAN 2024

## Trade name: Technovit 5000 liquid

(Contd. of page 4)

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

#### 14 Transport information

· Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)



· ADR/RID-GGVS/E Class: 3 (F1) Flammable liquids.

· Kemler Number: 339 · UN-Number: 1247 · Packaging group: // · Label 3

· Designation of goods: 1247 METHYL METHACRYLATE MONOMER, STABILIZED, solution

· Maritime transport IMDG/GGVSea:



· IMDG/GGVSea Class: 3 · UN Number: 1247 · Label 3

· Packaging group: || · EMS Number: F-E,S-L · Marine pollutant: No

· Correct technical name: METHYL METHACRYLATE MONOMER, STABILIZED, solution

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 · UN/ID Number: 1247 · Label 3

· Packaging group:

· Correct technical name: METHYL METHACRYLATE MONOMER, STABILIZED, solution

· Transport/Additional information: -

#### 15 Regulatory information

· Designation according to EC guidelines:

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)

· Code letter and hazard designation of product:

Xi Irritant

F Highly flammable

(Contd. on page 6)

JAN 2024

## Trade name: Technovit 5000 liquid

(Contd. of page 5)

#### · Hazard-determining components of labelling: methyl methacrylate

#### · Risk phrases:

Highly flammable.

37/38 Irritating to respiratory system and skin.

May cause sensitisation by skin contact. 43

#### Safety phrases:

9 Keep container in a well-ventilated place.

1∎Keep away from sources of ignition - No smoking.

24 Avoid contact with skin.

33 Take precautionary measures against static discharges.

37 Wear suitable gloves.

43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.

#### 16 Other information:

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## Relevant R-phrases

Highly flammable. Irritating to eyes.

36

36/37/38 Irritating to eyes, respiratory system and skin.

37/38 Irritating to respiratory system and skin.

May cause sensitisation by skin contact. 43

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.