

Telephone: (716) 282-6950 Fax: (716) 282-6971

January 2024

Technovit 4000 powder

page 2

Technovit 4000 Syrup 1

page 7



Telephone: (716) 282-6950 Fax: (716) 282-6971

January 2024

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: Technovit 4000 powder

SECTION 2. Composition/Data on components:

Chemical characterization

- · Description: -
- · Dangerous components:

94-36-0 dibenzoyl peroxide Xi, E; R 2-36-43 0-5%

· Additional information For the wording of the listed risk phrases refer to section 16.

SECTION 3. Hazards identification

Hazard description:

Xi ?@G Irritan t

· Information pertaining to particular dangers for man and environment

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. R 43 May cause sensitization by skin contact.

· Classification system

The classification was made according to the latest editions of the EU-lists, and expanded upon from company and literature data.

· NFPA ratings for USA (scale 0-4)



SECTION 4. First aid measures

After skin contact Immediately wash with water and soap and rinse thoroughly. After eye contact Rinse opened eye for several minutes under running water. After swallowing Induce vomiting and seek advice of physician.



Telephone: (716) 282-6950 Fax: (716) 282-6971

January 2024

SECTION 5. Fire fighting measures

Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards caused by the material, its products of combustion or resulting gases: Formation of toxic gases is possible during heating or in case of fire.
- · Protective equipment: No special measures required.

SECTION 6. Accidental release measures

- · Person-related safety precautions: Not required.
- · Measures for environmental protection: No special measures required.
- · Measures for cleaning/collecting: Pick up mechanically.
- · Additional information: No dangerous substances are released.

SECTION 7. Handling and storage

- · Handling
- · Information for safe handling: No special measures required.
- \cdot Information about protection against explosions and fires: No special measures required.
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep cool, if possible (not above 25 °C).
- · Storage class
- · Class according to regulation on flammable liquids: Void

SECTION 8. Exposure controls and personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- \cdot Components with limit values that require monitoring at the workplace: 94-36-0 dibenzoyl peroxide

 $TLV 5 mg/m^3$

- \cdot Additional information: The lists that were valid during the creation were used as basis.
- · Personal protective equipment
- · General protective and hygienic measures

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

- · Breathing equipment: Not required.
- · Protection of hands:

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

4011 Hyde Park Blvd.
P. O. Box 1075
Niagara Falls, NY 14302-1075

Telephone: (716) 282-6950 Fax: (716) 282-6971

January 2024

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further

marks of quality and varies from manufacturer to manufacturer. As the product is a preparation $\ \,$

of several substances, the resistance of the glove material can not be calculated in advance $\$

and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves

and has to be observed.

· For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR

Natural rubber, NR Chloroprene rubber, CR

 \cdot For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

PVC or PE gloves

· Eye protection: Not absolutely necessary.

· Body protection: Light weight protective clothing

SECTION 9. Physical and chemical properties:

- · General Information
- · Form: Powder · Color: Colorless
- · Odor: Odorless
- · Change in condition
- Melting point/Melting range: undetermined
 Boiling point/Boiling range: undetermined
- · Flash point: Not applicable
- · Auto igniting: Product is not selfigniting.
- · Danger of explosion: Product does not present an explosion hazard.
- · Density at 20°C: 2.650 g/cm³ · Bulk density at 20°C: 900 kg/m³
- · Solubility in / Miscibility with
- · Water: Insoluble
- · Solvent content:
- · Organic solvents: 0.0 %
- · Water: 0.1 %
- · Solids content: 100.0 %



Telephone: (716) 282-6950 Fax: (716) 282-6971 **January 2024**

SECTION 10. Stability and reactivity

- · Dangerous reactions No dangerous reactions known
- · Dangerous products of decomposition: none

SECTION 11. Toxicological information

- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

SECTION 12. Ecological information:

· General notes: Generally not hazardous for water.

SECTION 13. Disposal considerations

- · Product:
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Small quantities can be polymerized with the matching system component(s) and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities.

- Uncleaned packagings:
- · Recommendation: Packaging can be reused or recycled after cleaning.
- · DOT regulations:
- · Hazard class: -
- · Land transport ADR/RID (cross-border)
- · ADR/RID class: -
- · Maritime transport IMDG:
- · IMDG Class: -
- · Marine pollutant: No
- · Air transport ICAO-TI and IATA-DGR:
- · ICAO/IATA Class: -

SECTION 15. Regulations

· SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

· SARA Section 313 (specific toxic chemical listings)

94-36-0 dibenzoyl peroxide

· TSCA (Toxic Substances Control Act)

94-36-0 dibenzoyl peroxide

4011 Hyde Park Blvd. P. O. Box 1075 Niagara Falls, NY 14302-1075 Telephone: (716) 282-6950 Fax: (716) 282-6971 **January 2024**

84-61-7 dicyclohexyl phthalate

7732-18-5 water, distilled, conductivity or of similar purity

· Prop 65 - Chemicals known to cause cancer

None of the ingredients is listed.

Prop 65 - Chemicals known to cause reproductive toxicity

None of the ingredients is listed.

- · Cancerogenity categories
- EPA (Environmental Protection Agency)

None of the ingredients is listed.

· IARC (International Agency for Research on Cancer)

94-36-0 dibenzoyl peroxide 3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

94-36-0 dibenzoyl peroxide A4

MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Markings according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials

· Code letter and hazard designation of product:

Xi Irritant

· Hazard-determining components of labelling:

dibenzoyl peroxide

· Risk phrases:

43 May cause sensitization by skin contact.

· Safety phrases:

24 Avoid contact with skin.

37 Wear suitable gloves.

60 This material and its container must be disposed of as hazardous waste.

- · National regulations
- · Classification according to VbF: Void
- · Technical instructions (air):

Class Share in %

II 0-5

· Water hazard class: Generally not hazardous for water.

Telephone: (716) 282-6950 Fax: (716) 282-6971

January 2024

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: technovit 4000 Syrup 1

SECTION 2. Composition/Data on components:

Dangerous components:

100-42-5 styrene \Xn: R 10-20-36/38 25-50% 80-62-6 methyl methacrylate Xi, **F**; R 11-37/38-43 0-5%

SECTION 3. Hazards identification

Information pertaining to particular dangers for man and environment The product has to be labelled due to the calculation procedure of the "General Classification

quideline for preparations of the EU" in the latest valid version.

R 10 ${\it Flammable}.$

Harmful by inhalation. R 20

R 36/38 Irritating to eyes and skin.

May cause sensitization by skin contact.

Classification system

The classification was made according to the latest editions of the EU-lists, and expanded upon from company and literature data.

NFPA ratings for USA (scale 0-4)

SECTION 4. First aid measures

General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact Immediately wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. ■ After swallowing Induce vomiting and seek advice of physician.

SECTION 5. Fire fighting measures

Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. CO2, sand, extinguishing powder. Do not use water. For safety reasons unsuitable extinguishing agents Water. Water with full jet. Special hazards caused by the material, its products of combustion or resulting gases: Formation of toxic gases is possible during heating or in case of fire. Protective equipment: Mount respiratory protective device.



Telephone: (716) 282-6950 Fax: (716) 282-6971 **January 2024**

SECTION 6. Accidental release measures

■ Person-related safety precautions: Wear protective equipment. Keep unprotected persons away. Measures for environmental protection:

Prevent seepage into sewage system, workpits and cellars. Measures for cleaning/collecting:

Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues). Dispose contaminated material as waste according to item 13. Do not flush with water or aqueous cleansing agents Additional information: No dangerous substances are released.

SECTION 7. Handling and storage

Handling

Information for safe handling:.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Storage

Requirements to be met by storerooms and receptacles: Store in a cool location. Information about storage in one common storage facility: Not required. Further information about storage conditions:

Keep cool, if possible (not above 25 °C).

Store in cool, dry conditions in well sealed receptacles. Storage class

■ Class according to regulation on flammable liquids: A I

SECTION 8. Exposure controls and personal protection

Additional information about design of technical systems: No further data; see item 7. Components with limit values that require monitoring at the workplace:

100-42-5styrene . ~

TLV Short-term value: 852 mg/m3, 200 ppm Long-term value: 213 mg/m3, 50 ppm 80-62-6 methyl methacrylate ' $r\sim$

TLV 410 mg/m3, TOO ppm ' ~

• Additional information: The lists that were valid during the creation were used as basis.

Personal protective equipment

General protective and hygienic measures

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Breathing equipment:

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing \blacksquare protective mask (fitter A). Protection of hands:

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization. Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

4011 Hvde Park Blvd. P. O. Box 1075 Niagara Falls, NY 14302-1075 Telephone: (716) 282-6950 Fax: (716) 282-6971 January 2024

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g.

Laboratory) gloves made of the following material are suitable:

Wear protective gloves based on polyvinyl alcohole. .

For the permanent contact of a maximum Of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrite rubber, NBR Chloroprene rubber, CR

SECTION 9. Physical and chemical properties:

General Information

Fluid Form: Color: Colorless Characteristic Odor.

■ Change in condition

Melting point/Melting range:

undetermined Boiling point/Boiling

range: 100°C

Flash point: 10°C ■ Ignition temperature: 430°C

Auto igniting: . Product is not selfigniting.

■ Danger of explosion: Product is not explosive. However, formation of

explosive air/vapor mixtures are possible.

1.2 Vol% Explosion 12.5 Vol% limits: ■

Lower: Upper:

Vapor pressure at 20°C: 47hPa Density at 20"C: 1 g/cm^3

Solubility in 1 Not miscible or difficult to mix

Miscibility with Water:

Viscosity: 60 s (DIN 53211/4)

kinematic at 20"C:

■ Solvent content: 45.0 %

■ Organic

solvents: 55.0 %



Telephone: (716) 282-6950 Fax: (716) 282-6971

January 2024

SECTION 10. Stability and reactivity

■ Dangerous reactions No dangerous reactions known Dangerous products of decomposition: none Additional information: Product might polymerize after considerable exceeding of recommended storage time or temperature. .

11. Toxicological information SECTION

· Primary irritant effect:

on the skin: Irritant to skin and mucous membranes.

■ on the eye: Irritating effect.

■ Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

Harmful Irritant

The product shdws the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

SECTION 12. Ecological information:

General notes:

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13. Disposal considerations

Product:

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage

Small quantities can be polymerized with the matching system component(s) and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities.

Uncleaned packagings: ■ **Recommendation:** Disposal must be made according to official regulations. DOT regulations:

SECTION 15. DOT Regulations

Hazard class: 3

Identification number: UN1866

Packing group: III

Proper shipping name (technical name): RESIN SOLUTION

Label 394-36-0 dibenzoyl peroxide

4011 Hyde Park Blvd. P. O. Box 1075 Niagara Falls, NY 14302-1075

Telephone: (716) 282-6950 Fax: (716) 282-6971

January 2024

84-61-7 dicyclohexyl phthalate

7732-18-5 water, distilled, conductivity or of similar purity

· Prop 65 - Chemicals known to cause cancer

None of the ingredients is listed.

Prop 65 - Chemicals known to cause reproductive toxicity

None of the ingredients is listed.

- · Cancerogenity categories
- EPA (Environmental Protection Agency)

None of the ingredients is listed.

· IARC (International Agency for Research on Cancer)

94-36-0 dibenzoyl peroxide 3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

94-36-0 dibenzoyl peroxide A4

MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Markings according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials

· Code letter and hazard designation of product:

Xi Irritant

· Hazard-determining components of labelling:

dibenzoyl peroxide

· Risk phrases:

43 May cause sensitization by skin contact.

· Safety phrases:

24 Avoid contact with skin.

37 Wear suitable gloves.

60 This material and its container must be disposed of as hazardous waste.

- · National regulations
- · Classification according to VbF: Void
- · Technical instructions (air):

Class Share in %

II 0-5

· Water hazard class: Generally not hazardous for water.