

MET-MOUNT 2 RESIN

Safety Data Sheet

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
Trade name : MET-MOUNT 2 RESIN
CAS No : M336R
Product code :

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Resin: component
Recommended use : Industrial uses: Uses of substances as such or in preparations at industrial sites

1. Details of the supplier of the safety data sheet

METLAB CORPORATION
4011 HYDE PARK BLVD. NIAGARA FALLS
NY 14305 800-828-6866

1. Emergency telephone number

Emergency number : 813-248-0585 (Chem-Tel)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin corrosion/irritation Category 2	H315
Serious eye damage/eye irritation Category 2A	H319
Skin sensitization Category 1	H317
Hazardous to the aquatic environment - Acute Hazard Category 3	H402
Hazardous to the aquatic environment - Chronic Hazard Category 2	H411

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

GHS09

Signal word (GHS-US) :

: Warning

Hazard statements (GHS-US) :

: H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

: P261 - Avoid breathing mist/vapors/spray
P264 - Wash all contact areas thoroughly after handling
P272 - Contaminated work clothing must not be allowed out of the workplace
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection
P302+P352 - If on skin: Wash with plenty of mild soap and water
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P321 - Specific treatment: See SDS Section 4.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P391 - Collect spillage
P501 - Dispose of contents/container to special waste facility in accordance with regional/national regulations

MET-MOUNT 2 RESIN

Safety Data Sheet

2. Other hazards

No additional information available

2. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.O. Mixtures

Name	Product identifier	%	GHS-US classification
Bisphenol-A Epoxy Resin	(CAS No) 25068-38-6	>= 50	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 2, H411
Glycidyl ether blend	(CAS No) TRADE SECRET	< 50	Skin Irrit. 2, H315 Skin Sens. 1, H317
acrylate	(CAS No) 15625-89-5	< 50	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.
First-aid measures after skin contact	: Dispose of contaminated leather articles. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash clothing frequently. Keep work clothing separately. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Symptoms may be delayed.
Symptoms/injuries after inhalation	: Not expected to present a respiratory hazard under ambient conditions of normal industrial use due to low vapor pressure. Inhalation of vapors may cause respiratory irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause an allergic skin reaction. May cause sensitization by skin contact. Repeated or prolonged contact may cause injury to skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Inflammation/damage of the eye tissue. Swelling and conjunctivitis.
Symptoms/injuries after ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

acrylate (15625-89-5)	
Chronic symptoms	ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Skin rash/inflammation.
Glycidyl ether blend (TRADE SECRET)	
Chronic symptoms	Repeated and/or prolonged exposure may cause: Skin disorders and Allergies. Adverse skin effects (such as rash, irritation or corrosion).
Bisphenol-A Epoxy Resin (25068-38-6)	
Chronic symptoms	Allergic response, tissue swelling, hives.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

MET-MOUNT 2 RESIN

Safety Data Sheet

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Irritating and/or toxic gases or fumes likely if involved in fire or exposed to extreme heat.
Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : On burning: release of harmful/irritant gases/vapors.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses. Protective goggles.
Emergency procedures : Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Impermeable boots and protective equipment. Protective gloves. Safety glasses.
Emergency procedures : Stop leak if safe to do so. Prevent product from entering drains.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dike and contain spill. Soak up small spill with inert solids. Sweep or shovel spills into appropriate container for disposal.
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Clean contaminated surfaces with a soap solution.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : When heated, material emits irritating fumes.
Precautions for safe handling : Avoid contact with skin and eyes. Wear personal protective equipment. Avoid contact with eyes.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a dry place.
Maximum storage period : 12 months
Storage temperature : 15 - 50 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

acrylate (15625-89-5)

Not applicable

Aliphatic Glycidyl Ether (2461-15-6)

Not applicable

Glycidyl ether blend (TRADE SECRET)

Not applicable

MET-MOUNT 2 RESIN

Safety Data Sheet

Bisphenol-A Epoxy Resin (25068-38-6)

Not applicable

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Materials for protective clothing	: butyl rubber. chloroprene rubber. nitrile rubber.
Hand protection	: Protective gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Thermal hazard protection	: Use insulated gloves when handling this material hot.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: clear light yellow
Odor	: Mild odor nondescript
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: < 0 °C
Boiling point	: > 200 °C
Flash point	: > 100 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.11 g/cm ³
Solubility	: insoluble in water.
Log Pow	: No data available
Auto-ignition temperature	: > 300 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 500 cP 25 C
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

Minimum ignition energy	: No Data
-------------------------	-----------

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reaction with amines in large amounts or under uncontrolled conditions may produce extreme heat with noxious smoke and fumes.

MET-MOUNT 2 RESIN

Safety Data Sheet

10 ■ Conditions to avoid

Overheating.

10 ■ Incompatible materials

Oxidizing agent.

10 ■ Hazardous decomposition products

carbon oxides (CO and CO₂). Residual monomer.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

acrylate (15625-89-5)	
LD50 oral rat	5190 mg/kg (Rat)
LD50 dermal rabbit	5170 mg/kg (Rabbit)
ATE US (oral)	5190.000 mg/kg body weight
ATE US (dermal)	5170.000 mg/kg body weight
Aliphatic Glycidyl Ether (2461-15-6)	
LD50 oral rat	7800 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg
ATE US (oral)	7800.000 mg/kg body weight
Glycidyl ether blend (TRADE SECRET)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2150 mg/kg
Bisphenol-A Epoxy Resin (25068-38-6)	
LD50 oral rat	> 15000 mg/kg
LD50 dermal rat	23000 mg/kg

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Not expected to present a respiratory hazard under ambient conditions of normal industrial use due to low vapor pressure. Inhalation of vapors may cause respiratory irritation.

Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction. May cause sensitization by skin contact. Repeated or prolonged contact may cause injury to skin.

Symptoms/injuries after eye contact : Causes serious eye irritation. Inflammation/damage of the eye tissue. Swelling and conjunctivitis.

Symptoms/injuries after ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

acrylate (15625-89-5)	
Chronic symptoms	ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Skin rash/inflammation.

MET-MOUNT 2 RESIN

Safety Data Sheet

Glycidyl ether blend (TRADE SECRET)	
Chronic symptoms	Repeated and/or prolonged exposure may cause: Skin disorders and Allergies. Adverse skin effects (such as rash, irritation or corrosion).
Bisphenol-A Epoxy Resin (25068-38-6)	
Chronic symptoms	Allergic response, tissue swelling, hives.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects. Harmful to aquatic life.

Bisphenol-A Epoxy Resin (25068-38-6)	
LC50 fish 1	2 mg/l (96 h; Oncorhynchus mykiss; Lethal)
EC50 Daphnia 1	2.8 mg/l (48 h; Daphnia magna; Locomotor effect)
LC50 fish 2	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
EC50 Daphnia 2	1.8 mg/l (48 h; Daphnia magna)
ErC50 (algae)	11 mg/l Scenedesmus Growth rate inhibition carpicornutum (fresh water algae)
NOEC (chronic)	0.3 mg/l Daphnia Magna, Fresh water 21 days (OECD 211 equivalent)
NOEC chronic fish	0.351 ng/l Pimephales promela, Fresh water, 32 days
NOEC chronic crustacea	0.32 ng/l Daphnia Magna, Fresh water semi-static, 21 days

12.2 Persistence and degradability

acrylate (15625-89-5)	
Persistence and degradability	Biodegradability in water: no data available.
ThOD	1.835 g O ₂ /g substance
Glycidyl Ether	
Persistence and degradability	Biodegradability in water: no data available.
Biochemical oxygen demand (BOD)	0.14 g O ₂ /g substance
Chemical oxygen demand (COD)	2.46 g O ₂ /g substance
ThOD	2.66 g O ₂ /g substance
BOD (% of ThOD)	0.0526
Glycidyl ether blend (TRADE SECRET)	
Persistence and degradability	Biodegradability in water: no data available.
Bisphenol-A Epoxy Resin (25068-38-6)	
Persistence and degradability	not readily degradable in water.

12.3. Bioaccumulative potential

acrylate (15625-89-5)	
Log Kow	0.67 23 C
Bioaccumulative potential	No bioaccumulation data available.
Glycidyl ether blend (TRADE SECRET)	
Log Pow	2.97 Estimated
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Bisphenol-A Epoxy Resin (25068-38-6)	
BCF fish 1	3 - 31 QSAR
Log Pow	3.242 estimated
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Bisphenol-A Epoxy Resin (25068-38-6)	
Surface tension	0.0 587-0.0589, 20 °C

MET-MOUNT 2 RESIN

Safety Data Sheet

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Landfilling of free liquid not recommended. Fuels burning or incineration preferred for material disposed of in "as sold" condition if regulations permit.
Sewage disposal recommendations : Do not discharge into drains or the environment.
Waste disposal recommendations : Collect all waste in suitable and labeled containers and dispose according to local legislation.
Additional information : Industrial waste. Landfilling of free liquid not recommended. Fuels burning or incineration preferred for material disposed of in "as sold" condition if regulations permit.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT
Not regulated in non-bulk quantities by road or air in the continental U.S.

Transport by sea

UN-No. (IMDG) : 3082
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A Epoxy Resin)
Class (IMDG) : 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : 5 L
Marine pollutant : Yes (IMDG only)



Air transport

UN-No. (IATA) : 3082
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s. Bisphenol-A Epoxy Resin)
Class (IATA) : 9 - Miscellaneous Dangerous Goods
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Epoxy Resin 20065 (None - mix)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

acrylate (15625-89-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Reactive hazard

Aliphatic Glycidyl Ether (2461-15-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

MET-MOUNT 2 RESIN

Safety Data Sheet

Glycidyl ether blend (TRADE SECRET)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

Bisphenol-A Epoxy Resin (25068-38-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C))
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

15.2. International regulations

CANADA

Epoxy Resin 20065 (None - mix)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

Epoxy Resin 20065 (None - mix)	
RoHS Substance	No
SVHC	No

acrylate (15625-89-5)	
SVHC	No
RoHS Substance	No

Glycidyl ether blend (TRADE SECRET)	
SVHC	No
RoHS Substance	No

Bisphenol-A Epoxy Resin (25068-38-6)	
SVHC	No
RoHS Substance	No

National regulations

Epoxy Resin 20065 (None - mix)	
All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory	

15.3. US State regulations

No additional information available

SECTION 16: Other information

Other information : DISCLAIMER: To the best of our knowledge, the information contained in this MSDS is accurate or is obtained from sources believed to be accurate. However, no liability, expressed or implied, is assumed for the accuracy or completeness of the information contained herein. Buyer assumes liability in its use of the material.

Full text of H-phrases:

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects

Abbreviations and acronyms:

MET-MOUNT 2 RESIN

Safety Data Sheet

N.A. - Not Applicable
N.E. - Not Established
N.D. - Not Determined
ACGIH = American Conference of Governmental Industrial Hygienists
OSHA = US Occupational Health and Safety Administration
TLV-TWA = Threshold Limit Value-Time Weighted Average (8 hrs)
STEL = Short-Term Exposure Limit (15 min)
C = Ceiling Value
PEL = Permissible Exposure Limit
OEL = Occupational Exposure Limit
IDLH = Immediately Dangerous to Life and Health
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
PNEC = Predicted No Effect Concentration
LOAEL = Lowest Observed Adverse Effect Level
NOAEL = No Observed Adverse Effect Level
NOAEC = No Observed Adverse Effect Concentration

NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection

: C

C - Safety glasses, Gloves, Synthetic apron

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product