

MATERIAL SAFETY DATA SHEET



4011 Hyde Park Blvd.
P. O. Box 1075
Niagara Falls, NY 14302-1075

Telephone: (716) 282-6950
Fax: (716) 282-6971

January 2025

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT NAME
Aluminum Oxide Vitrified Product

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE DESCRIPTION	PERCENT	CAS#
Aluminum Oxide, Non-fibrous	30.000- 97.000	1344-28-1
Amorphous Silica, Fused	2.000- 35.000	60676-86-0
OTHER		
Not Applicable		

SECTION 3. HAZARDS IDENTIFICATION

INHALATION ACUTE EXPOSURE EFFECTS
Dust may be slightly irritating to eyes and respiratory tract at high concentrations.

INHALATION CHRONIC EXPOSURE EFFECTS
May affect breathing capacity. For products containing Amorphous Silica, Fused, there is limited evidence in animals that excessive and prolonged exposure to this chemical may cause pulmonary fibrosis.

EYE CONTACT ACUTE EXPOSURE EFFECTS
Dust may irritate eyes.

SKIN CONTACT ACUTE EXPOSURE EFFECTS
Some may experience skin irritation from dust.

INGESTION ACUTE EXPOSURE EFFECTS
No known adverse effects, but ingestion not recommended.

SECTION 4. FIRST AID MEASURES

INHALATION
Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately.

SKIN CONTACT
Wash affected areas with soap and water. Obtain medical assistance.

EYE CONTACT
Wash with large amounts of water. Obtain first aid and medical assistance, if needed.

INGESTION
Call poison control center, hospital emergency room or physician immediately.



SECTION 5. FIRE FIGHTING MEASURES

FIRE FIGHTING PROCEDURES

Not Applicable

HAZARDOUS PRODUCTS/COMBUSTION

None.

HAZARD RATING SOURCE

NFPA

HEALTH

1

FLAMMABILITY

0

REACTIVITY

0

OTHER

SECTION 6. ACCIDENTAL RELEASE MEASURES

CLEAN-UP

Follow normal clean up procedures.

SECTION 7. HANDLING AND STORAGE

HANDLING

Always HANDLE AND STORE wheels in a CAREFUL manner.

Always VISUALLY INSPECT all wheels before mounting.

Always CHECK MACHINE SPEED against the established maximum safe operating speed MARKED ON THE WHEEL.

Always CHECK MOUNTING FLANGES for equal and correct diameter.

Always USE MOUNTING BLOTTERS.

Always be sure WORK REST is properly adjusted.

Always USE A SAFETY GUARD covering at least one-half of the grinding wheel.

Always allow NEWLY MOUNTED WHEELS to run at operating speed, with guard in place, for at least one minute before grinding.

Always TURN OFF COOLANT before stopping wheel to avoid creating an out-of-balance wheel

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION PROTECTION

Recommend using local exhaust ventilation when general ventilation is not keeping the airborne concentration below the TLV.

RESPIRATORY PROTECTION

Respirators are required when airborne contaminant levels exceed the TLV(s).

MATERIAL SAFETY DATA SHEET



4011 Hyde Park Blvd.
P. O. Box 1075
Niagara Falls, NY 14302-1075

Telephone: (716) 282-6950
Fax: (716) 282-6971

January 2025

EYE PROTECTION

Always WEAR SAFETY GLASSES or some type of eye protection when grinding.

OTHER PROTECTION

Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR

Solid article. Odorless.

SECTION 10. STABILITY AND REACTIVITY

INCOMPATIBILITIES

Avoid acids of all types with a pH < 4.0.

DECOMPOSITION

In use, dusts and decomposing odors may be generated. In most cases, the material removed from the workpiece will be significantly greater than the grinding wheel components. Coolants may produce other decomposition products.

For products containing phenol and formaldehyde resin, thermal decomposition may produce trace amounts of phenol and formaldehyde.

For products containing inorganic fluorides, thermal decomposition may produce trace amounts of fluorides.

SECTION 11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY

Silica, Amorphous, Fused - IARC-3, NIOSH-X
LD50/LC50

Values are not appropriate or available.

SECTION 12. ECOLOGICAL INFORMATION

CHEMICAL FATE

Vitrified products do not appreciably decay.

SECTION 13. DISPOSAL CONSIDERATIONS

MATERIAL SAFETY DATA SHEET



4011 Hyde Park Blvd.
P. O. Box 1075
Niagara Falls, NY 14302-1075

Telephone: (716) 282-6950
Fax: (716) 282-6971

January 2025

WASTE DISPOSAL

Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

Products with listed flourides may have slightly soluble flouride swarf.

RECYCLING PROGRAM - the Company has developed a grinding wheel recycling program. If you are interested in returning your stubs, information can be obtained by dialing Customer Service.

SECTION 14. TRANSPORT INFORMATION

HAZARD CLASS

This product is not hazardous as defined by the Department of Transportation.(USA)

This product is "Not Regulated" under the Transportation of Dangerous Goods Act. (CAN)

SECTION 15. REGULATORY INFORMATION

EXPOSURE LIMITS/REGULATORY INFORMATION

SUBSTANCE DESCRIPTION	UNITS	OSHA	ACGIH	MOL
Aluminum Oxide, Non-fibrous	MG/M3	15.0000	10.0000	10.0000
Amorphous Silica, Fused	MG/M3	0.1000	0.1000	0.0000

LEGEND:

EXPOSURE LIMIT DESCRIPTIONS

CA PROP 65

Not Applicable

TSCA

Section 8(b) - Inventory Status

All components of this product are registered under the regulations of the Toxic Substance Control Act.

DOMESTIC SUBSTANCE LIST

All components of this product are found on the Domestic Substance List.

SECTION 16. OTHER INFORMATION

MATERIAL SAFETY DATA SHEET



4011 Hyde Park Blvd.
P. O. Box 1075
Niagara Falls, NY 14302-1075

Telephone: (716) 282-6950

Fax: (716) 282-6971

January 2025

DISCLAIMER

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof; however, the Company makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

KEY TO ABBREVIATIONS:

EQ=Equal

AP=Approximately

=

LT=Less Than

TR=Trace

GT=Greater Than

ND=No Data available